No. 1907/2006 (REACH) Printed 12.03.2018

revision 12.03.2018 (GB) Version 1.0

Clear a Ship Power Cleaner



SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Name of product Clear a Ship Power Cleaner
Art-Nr 1.0201.07195.00000

1.2. Relevant identified uses of the substance or mixture and uses advised against Recommended intended purpose(s)

cleaning agent

1.3. Details of the supplier of the safety data sheet

Manufacturer/distributor Yachticon A. Nagel GmbH

Bürgermeister-Bombeck-Str. 1, D-22851 Norderstedt

Phone +49 40 511 3780, Fax +49 40 51 74 37

E-Mail yachticon@yachticon.de Internet www.yachticon.de

Advice

Phone +49 40 511 37 80 Fax +49 40 51 74 37 E-mail (competent person): yachticon@yachticon.de

1.4. Emergency telephone number

Emergency advice Giftinformationszentrale Berlin

Phone +49 (0)30 30686700 Information in German.

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP/GHS]

Statements

Hazard classes and Hazard

Hazard

Classification procedure

categories

Skin Corr. 1B

H314

Hazard statements for health hazards

H314 Causes severe skin burns and eye damage.

Additional hints

This mixture is classified as hazardous according to Regulation (EC) No 1272/2008 [GHS].

2.2. Label elements

Labelling according to Regulation (EC) No 1272/2008 [CLP/GHS]



GHS05

Signal word

Danger

No. 1907/2006 (REACH) Printed 12.03.2018

revision 12.03.2018 (GB) Version 1.0

Clear a Ship Power Cleaner



Hazard statements for health hazards

H314 Causes severe skin burns and eye damage.

Precautionary Statements

General

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

Prevention

P260 Do not breathe gas/vapours/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

Response

P301 + P330 + IF SWALLOWED: rinse mouth. Do NOT induce vomiting.

P331

P303 + P361 + IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse

P353 skin with water/shower.

P305 + P351 + IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses,

P338 if present and easy to do. Continue rinsing.
P310 Immediately call a POISON CENTER/doctor/....
P363 Wash contaminated clothing before reuse.

Storage

P405 Store locked up.

Disposal

P501 Dispose of contents/container to an approved waste handling.

Hazardous ingredients for labeling

potassium-hydroxide, sodium metasilicate 5-hydrate

Additional information

Special rules on packaging

Touchable warning sign (EN/ISO 11683). Childproof closures (EN/862/ISO 8317).

2.3. Other hazards

Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

SECTION 3: Composition/information on ingredients

3.1. Substances

not applicable

3.2. Mixtures

Hazardous ingredients

CAS No	EC No	Name	[% weight]	Classification according to Regulation (EC) No 1272/2008 [CLP/ GHS]
111-76-2	203-905-0	2-butoxyethanol	< 2	Acute Tox. 4, H332 / Acute Tox. 4, H312 / Acute Tox. 4, H302 / Eye Irrit. 2, H319 / Skin Irrit. 2, H315
112-34-5	203-961-6	2-(2-butoxyethoxy)ethanol	< 2	Eye Irrit. 2, H319
122-99-6	204-589-7	2-phenoxyethanol	< 3	Acute Tox. 4, H302 / Eye Irrit. 2, H319

No. 1907/2006 (REACH) Printed 12.03.2018

revision 12.03.2018 (GB) Version 1.0

Clear a Ship Power Cleaner



CAS No	EC No	Name	[% weight]	Classification according to Regulation (EC) No 1272/2008 [CLP/ GHS]
1310-58-3	215-181-3	potassium-hydroxide	2,5	Acute Tox. 4, H302 / Skin Corr. 1A, H314
10213-79-3		sodium metasilicate 5-hydrate	1,5	Skin Corr. 1B, H314 / STOT SE 3, H335 / Met. Corr. 1, H290
15763-76-5		Cumene sulfonate (sodium salt)	< 2	Eye Irrit. 2, H319
164524-02-1	629-764-9	Cumene sulfonate (potassium salt)	< 2	Eye Irrit. 2, H319
REACH				
CAS No	Name			REACH registration number
1310-58-3	potassium-hy	/droxide		01-2119487136-33-XXXX
15763-76-5	Cumene sulfonate (sodium salt)			01-2119489411-37-0000
164524-02-1	Cumene sulfonate (potassium salt)			01-2119489427-24-0000

Additional advice

Labelling for contents according to regulation (EC) No 648/2004, annex VII

less than 5 % anionic surfactants less than 5 % non-ionic surfactants

PHENOXYETHANOL

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Remove contaminated soaked clothing immediately and dispose it safely.

In case of accident or if you feel unwell seek medical advice immediately (if possible show directions for use or safety data sheet).

In case of inhalation

Seek medical advice immediately.

Rinse mouth and nose with water.

Move the victim to fresh air and keep warm and calm.

In case of skin contact

Rinse with plenty of water.

Immediate medical treatment necessary, as untreated burns can result in slow-healing wounds.

In case of eye contact

In case of contact with eyes rinse thoroughly with water.

Remove contact lenses.

Call for a doctor immediately.

In case of ingestion

Call for a doctor immediately.

Rinse out mouth and give plenty of water to drink.

Do NOT induce vomiting - risk of perforation!

4.2. Most important symptoms and effects, both acute and delayed

No information available.

^{**} Substance-specific threshold values were taken into account for the classification of the product.

No. 1907/2006 (REACH) Printed 12.03.2018

revision 12.03.2018 (GB) Version 1.0

Clear a Ship Power Cleaner



4.3. Indication of any immediate medical attention and special treatment needed

No information available.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Product does not burn, fire-extinguishing activities according to surrounding.

Alcohol-resistant foam

Dry powder

Carbon dioxide

Water spray jet

5.2. Special hazards arising from the substance or mixture

In the case of thermal decomposition formation of dangerous gases possible.

Nitrogen oxides (NOx)

Carbon monoxide (CO)

Carbon dioxide (CO2)

Sulfur oxide

Acidic solutions may release corrosive fumes.

Attention slip hazard, if leaking.

Alkalische Lösungen können ätzende Dämpfe freisetzen.

5.3. Advice for firefighters

Special protective equipment for fire-fighters

Use breathing apparatus with independent air supply (isolated).

Wear full protective clothing.

Additional information

Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.

Collect contaminated firefighting water separately, must not be discharged into the drains.

Cool containers with water.

Remove containers from the danger area, if possible without risk.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures For non-emergency personnel

Ensure adequate ventilation.

Use personal protective clothing.

Do not breathe vapors.

Avoid contact with clothing, skin and eyes.

Warn persons who are present in the danger zone.

Keep unprotected persons away.

Use suitable breathing apparatus if exposed to vapors / aerosol.

6.2. Environmental precautions

Do not discharge into the drains/surface waters/groundwater.

Dilute with plenty of water.

Suppress gases/vapours/mists with water spray jet

No. 1907/2006 (REACH) Printed 12.03.2018

revision 12.03.2018 (GB) Version 1.0

Clear a Ship Power Cleaner



6.3. Methods and material for containment and cleaning up

Pump off larger quantity.

Send in suitable containers for recovery or disposal.

Take up with absorbent material (e.g. sand, general-purpose binder, kieselguhr).

Flush away residues with water.

After taking up the material dispose according to regulation.

Ensure adequate ventilation. Use neutralizing agent (acid).

6.4. Reference to other sections

Safe handling: see section 7 Disposal: see section 13

Personal protection equipment: see section 8 Emergency telephone number: see section 1

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Care for thoroughly room ventilation, if necessary use in well ventilated area with local exhaust ventilation at workplace.

Handle in accordance with good industrial hygiene and safety practice.

Do not inhale vapors.

Keep container tightly closed.

Do not eat, drink or smoke in the area of application.

Avoid mixing with acids / acid products ABSOLUTELY!

General protective measures

Avoid contact with eyes and skin

Do not inhale gases/vapours/aerosols.

Hygiene measures

Clean skin thoroughly after working.

At work do not eat, drink and smoke.

Remove soiled or soaked clothing immediately.

Work in rooms with good ventilation.

Wash hands before breaks and after work.

Use barrier skin cream.

Advice on protection against fire and explosion

No special measures required.

7.2. Conditions for safe storage, including any incompatibilities Requirements for storage rooms and vessels

Keep in closed original container.

Provide floor with bunding.

Further information on storage conditions

Protect from extreme heat and cold.

Keep container in a well-ventilated place

Keep container tightly closed and store at a cool and dry place.

Storage group 8B

No. 1907/2006 (REACH) Printed 12.03.2018

revision 12.03.2018 (GB) Version 1.0

Clear a Ship Power Cleaner



Remark

skin

7.3. Specific end use(s)

No information available.

SECTION 8: Exposure controls/personal protection

2-butoxyethanol

8.1. Control parameters

CAS No

111-76-2

Indicative occupational exposure limit values (91/322/EEC, 2000/39/EC, 2006/15/EC or 2009/161/EU)

[mg/m3]

98

[ppm]

20

Code

8 hours

BGW	Examination	
	material	Test date
gsäure 200 mg/l	U	C C
Code	Remark	
DNEL long-term dermal (system	mic)	
B DNEL long-term inhalative (systemic)		
1 mg/m3 DNEL long-term inhalative (local)		
Code	Remark	
DNEL long-term dermal (system	mic)	
DNEL long-term oral (repeated))	
B DNEL long-term inhalative (systemic)		
DNEL long-term inhalative (loc	al)	
Code	Remark	
PNEC sewage treatment plant	(STP)	
PNEC aquatic, marine water		
PNEC aquatic, freshwater		
g	Code DNEL long-term inhalative (systemic) DNEL long-term inhalative (loc Code DNEL long-term inhalative (loc DNEL long-term oral (repeated DNEL long-term inhalative (systemic) DNEL long-term inhalative (systemic) DNEL long-term inhalative (systemic) DNEL long-term inhalative (loc Code PNEC sewage treatment plant PNEC aquatic, marine water	igsäure 100 mg/l U igsäure 200 mg/l U U rolyse) Code Remark DNEL long-term dermal (systemic) DNEL long-term inhalative (systemic) DNEL long-term inhalative (local) Code Remark DNEL long-term dermal (systemic) DNEL long-term dermal (repeated) DNEL long-term inhalative (systemic) DNEL long-term inhalative (systemic) DNEL long-term inhalative (systemic) DNEL long-term inhalative (systemic) DNEL long-term inhalative (local) Code Remark PNEC sewage treatment plant (STP) PNEC aquatic, marine water

8.2. Exposure controls Respiratory protection

Breathing apparatus in the event of aerosol or mist formation.

Not necessary with adequate exhaust ventilation.

No. 1907/2006 (REACH) Printed 12.03.2018

revision 12.03.2018 (GB) Version 1.0

Clear a Ship Power Cleaner



Hand protection

Glove material specification [make/type, thickness, permeation time/life, wetting resistance]: Nitril, 0,4 mm, 60 min, 480 min. e.g. "Camatril Profi" (KCL GmbH, Email: Vertrieb@kcl.de)

The selection of the suitable gloves does not only depend on different material, but also on further marks of quality and varies from manufacturer to manufacturer.

The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

Eye protection

tightly fitting goggles

Other protection measures

protective clothing

Appropriate engineering controls

Ensure good ventilation, where necessary use fume hood.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

AppearanceColourOdourliquidcolourlessodourless

Tomporaturo

Mothod

Odour threshold not determined

Important health, safety and environmental information

Value

	Value	Iemperature	at	Method	Remark
pH value	13 - 14	20 °C			
boiling point	ca. 100 °C				
Melting point / Freezing point	not determined				
Flash point	not determined				
Vapourisation rate	not determined				
Flammable (solid)	not determined				
Flammability (gas)	not determined				
Ignition temperature	> 240 °C				
Self ignition temperature					The product is not self-igniting.
Lower explosion limit	not determined				
Upper explosion limit	not determined				
Vapour pressure	23 hPa	20 °C			

Domark

No. 1907/2006 (REACH)

Printed 12.03.2018

revision 12.03.2018 (GB) Version 1.0

Clear a Ship Power Cleaner



	Value	Temperature	at	Method	Remark
Relative density	ca. 1 g/cm3	20 °C			
Vapour density	not determined				
Solubility in water		20 °C			multimiscible
Solubility/other	not determined				
Partition coefficient noctanol/water (log PO/W)	not determined				
Decomposition temperature	not determined				
Viscosity	not determined				
Oxidising properties No information available.					
Explosive properties The product is not explosive	/e.				
9.2. Other information Refer to technical data she	eet.				

SECTION 10: Stability and reactivity

10.1. Reactivity

No information available.

10.2. Chemical stability

Stable under normal conditions of use.

Stable under recommended storage conditions.

10.3. Possibility of hazardous reactions

Reactions with acids.

Reactions with oxidising agents.

10.4. Conditions to avoid

Avoid heat and frost.

10.5. Incompatible materials

Substances to avoid

Acid

Oxidising agent

10.6. Hazardous decomposition products

Concerning possible decomposition products see section 5.

No. 1907/2006 (REACH) Printed 12.03.2018

revision 12.03.2018 (GB) Version 1.0

Clear a Ship Power Cleaner



Thermal decomposition

Remark No decomposition if used as directed.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity/Irritation/Sensitization

	Value/Validation	Species	Method	Remark
Skin irritation	corrosive			
Eye irritation	corrosive			
Skin sensitization	No known sensitization.			
Sensitization respiratory system	No known sensitization.			

Experiences made from practice

Corrosive effect on skin and mucous membrane.

If swallowed: Severe burns of the mouth and throat and to the danger of perforation of the esophagus and stomach.

Additional information

The product should be handled with the care usual when dealing with chemicals.

Further hazardous properties can not be excluded.

SECTION 12: Ecological information

12.1. Toxicity

No information available.

12.2. Persistence and degradability

No information available.

12.3. Bioaccumulative potential

No information available.

12.4. Mobility in soil

No information available.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Other adverse effects

Harmful effect in the water possible by shifting of the pH value.

Behaviour in sewage plant

The product is an alkaline solution. Neutralization is normally necessary before waste water is discharged into sewage treatment plants.

No. 1907/2006 (REACH) Printed 12.03.2018

revision 12.03.2018 (GB) Version 1.0

Clear a Ship Power Cleaner



General regulation

Ecological dates are not available.

Product is not allowed to be discharged into the ground water or aquatic environment.

The surfactant(s) contained in this preparation complies(comply) with the biodegradability criteria as laid down in Regulation (EC) No.648/2004 on detergents.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Recommendations for the product

There are no harmonised regulations on the disposal of chemicals in the member states of the EU. In Germany the Recycling and Waste Management Act (KrWG) stipulates recycling as a requirement. This means that a distinction must be made between "wastes for recycling" and "wastes for disposal". Particular aspects - in the main concerning delivery - are also governed by the Laender.

Recommendations for packaging

Disposal according to official regulations.

Recommended cleansing agent

water

General information

Allocation of the waste number has to be done according to the EWC directive industry- and process-specific.

SECTION 14: Transport information

	ADR/RID	IMDG	IATA-DGR
14.1. UN number	1719	1719	1719
14.2. UN proper shipping name	CAUSTIC ALKALI LIQUID, N.O.S. (Kaliumhydroxid, Natriummetasilikat)	CAUSTIC ALKALI LIQUID, N.O.S. (potassium hydroxide, sodium metasilicate)	Caustic alkali liquid, n.o.s. (potassium hydroxide, sodium metasilicate)
14.3. Transport hazard class(es)	8	8	8
14.4. Packing group	III	III	III
14.5. Environmental hazards	No	No	No

14.6. Special precautions for user

No information available.

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code No information available.

Land and inland navigation transport ADR/RID

Hazard label(s) 8 tunnel restriction code E Classification code C5

No. 1907/2006 (REACH) Printed 12.03.2018

revision 12.03.2018 (GB) Version 1.0

Clear a Ship Power Cleaner



SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations

Water hazard class 1 following AwSV (Germany) slightly hazardous to water

15.2. Chemical Safety Assessment

No information available.

SECTION 16: Other information

Training advice

See the technical data sheet for more information.

Recommended uses and restrictions

National and local regulations concerning chemicals shall be observed.

Further information

The national special regulations have to be implemented by each user their own responsibility! The information contained herein is based on the state of our knowledge. It characterizes the product with regard to the appropriate safety precautions. It does not represent a guarantee of the properties of the product.

Please note: Our Material Safety Data Sheets have been prepared in accordance with EU directives, WITHOUT taking into account the specific national regulations for handling hazardous materials and chemicals.

Sources of key data used

Data sheets of the suppliers.

European Chemicals Agency (ECHA)

Full text of the hazard phrases in section 2 and 3.

Federal Environment Agency (water hazard classes)

H290	May be corrosive to metals.
H302	Harmful if swallowed.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.